

COMPACT,
POWERFUL
& EFFICIENT

The Kartar 4036 is designed for efficiency and versatility, powered by a Kirloskar 3-cylinder, 2430 cc engine for smooth and reliable performance. Its 8+2 transmission with a single clutch ensures seamless gear shifting, while oil-immersed brakes enhance control and safety. With a 1800 kg lifting capacity and Category-II ADDC hydraulics, it provides precise implement handling for diverse farming applications..



TECHNICAL SPECIFICATIONS

ENGINE

Type: Kirloskar 3R 810, 2200 RPM, 3 Cylinder, Naturally aspirated.
Bore/stroke: 96 x 112 (2430 cc)
Air Filter: Dry Type Filter with Choke Sensor
Cooling: Copper Radiator with Coolant - Cooled System & Overflow Reservoir

TRANSMISSION

Clutch: Single
Gear Box: 8 Forward + 2 Reverse
Speeds: Forward 2.52 to 31.97
Reverse 3.53 to 13.90

BRAKES

Type: Oil Immersed Brakes

HYDRAULICS

Maximum Lifting Capacity: 1800Kgf
3 Point Linkage: Category-II Automatic Depth & Draft Control (ADDC)

STEERING

Type: Power steering/Mechanical (optional)

POWER TAKE OFF

Type: 540, 6 Splines

WHEELS AND TYRES

Front: 6.0 x 16
Rear: 13.6 x 28

FUEL TANK

Capacity 55L

ELECTRICAL SYSTEM

Battery 75Ah, 12V
Alternator 36 Amp.
Starter Motor 2.3 kW, 12V

DIMENSIONS AND WEIGHT

Total Weight: 1955 Kg
Wheel Base: 2015 mm
Overall Length: 3765 mm
Overall Width: 1740 mm
Track Width: 1395 mm
Ground Clearance: 420 mm

ACCESSORIES*

Tool Kit • Drawbar • Tow Hook • Top Link • Bumper

FEATURES

500 Hours Service Interval



Powerful kirloskar Engine

Powerful and fuel-efficient engine, delivering reliable performance with lower maintenance costs.



Radiator with Overflow Reservoir

Maintains optimal engine temperature and prevents overheating for uninterrupted performance.



Dry Type Filter with Choke Sensor

Ensures clean air intake for engine efficiency and longevity. Equipped with a choke sensor to indicate filter clogging for optimal performance.



E-Brochure

KARTAR GENUINE PARTS
Economical | Reliable | Easily Available

500 HOUR
SERVICE INTERVAL