

KARTAR**5936****KARTAR**

Since 1975

GLOBETRAC

WE DELIVER PERFORMANCE YOU LEAD




KIRLOSKAR 4 CYLINDER ENGINE

The Kirloskar 4R 1040 is a 4-cylinder, naturally aspirated engine with 2200 RPM, 4160 CC displacement, and 232 Nm torque, ensuring high power, efficiency, and reliability in all field conditions.



MITA HYDRAULICS

The 2200 KG MITA Hydraulic System ensures superior lifting for heavy implements. With the Lift-O-Matic Button, it enables quick and effortless operation.



CARRARO TRANSMISSION

Equipped with a Carraro Synchro Shuttle transmission, it provides 12 -forward and 12 reverse speeds, ensuring smooth and efficient gear shifting for optimal performance.

Technical Specification

KARTAR**5936**

ENGINE

Type:	Kirloskar 4R 1040, 2200 RPM, 4 Cylinder, Naturally aspirated.
Bore/stroke:	105 x 120 (4160 CC)
Torque:	232 Nm
Air Filter:	Dry Type Filter with Choke Sensor
Cooling:	Copper Radiator with Coolant - Cooled System & Overflow Reservoir

TRANSMISSION

Clutch:	Independent
Gear Box:	Carraro Synchro Shuttle Transmission 12 Forward + 12 Reverse
Speeds:	Forward 1.72 to 35.47 Reverse 1.46 to 30.15

BRAKES

Type:	Oil Immersed Brakes
-------	---------------------

HYDRAULICS

Maximum Lifting Capacity:	2200Kgf
3 Point Linkage:	Category-II Automatic Depth & Draft Control (ADDC) Lift-o-Matic Button

STEERING

Type:	Balanced Power Steering
-------	-------------------------

POWER TAKE OFF

Type:	540, 540E, 6 Splines, Ground Speed PTO
-------	--

WHEELS AND TYRES

	2WD	4WD
Front:	7.5 x 16	9.5 x 24
Rear:	16.9 x 28	16.9 x 28

FUEL TANK

Capacity	60L
----------	-----

ELECTRICAL SYSTEM

Battery	100Ah, 12V
Alternator	55 Amp.
Starter Motor	2.7 kW, 12V

DIMENSIONS AND WEIGHT

	2WD	4WD
Total Weight: (Incl. Accessories)	2670 Kg	3030 Kg
Wheel Base:	2290 mm	2290 mm
Overall Length:	4030 mm	4030 mm
Overall Width:	1920 mm	1920 mm
Track Width:	1475 mm	1475 mm
Ground Clearance:	375 mm	375 mm

ACCESSORIES*

Tool Kit • Drawbar • Tow Hook • Top Link • Bumper

FEATURES

- 500 Hours Service Interval • Battery cut off switch
- Spacious Platform • Heat Guard • Water Separator
- ROPS & Canopy (Optional)

Powerful, technologically advanced, KIRLOSKAR 4R 1040 ENGINE

- High Torque Across The Operating Speed Range
- Maximum Backup Torque Upto 45%


500 HOUR

SERVICE INTERVAL



Heavy Duty Chassis Support

Built for maximum durability and strength, ensuring long-lasting performance even in tough conditions.



Spacious Platform

Designed for enhanced comfort and convenience, providing ample space for operators during extended work hours.



BANCO Copper Radiator

Provides superior cooling, preventing engine overheating during prolonged field operations, even in extreme weather conditions.

KARTAR TRACTORS PRIVATE LIMITED

Shop No.22, Grain Market, Bhadson, Patiala.
Punjab, 147202

For more information, Please contact our Authorized Dealer or call our Customer Care.

KARTAR GENUINE PARTS

Economical | Reliable | Easily Available



E-Brochure

Images used in this product brochure are for reference purposes only.
Vehicle body colour may differ from the printed or digital photographs.

Call us:- 911 563 3336
To Know more about Kartar Tractors log on to www.kartartractors.com